



## Product Specifications

### Mineral Turpentine Oil (MTO)

#### CERTIFICATE OF ANALYSIS

TEST	TEST METHOD/TECHNIQUE	UNIT	RESULTS
Viscosity @40	ASTM D7042	cP	0.5-1
Sulphur content	ASTM D4294	mg /L	0.2-0.4
Appearance	Physical	-	colorless, clear & bright
Specific Gravity @15.56C	ASTM D4052	-	0.785
Flash Point	ASTM D93-A	-	38-42
Acidity	ASTM D3242	mg KOH/gm	Neutral
Initial boiling point (IBP)	ASTM D1120	°C	140
10°.» - collected boiling point	ASTM D1120	°C	-
20°.» - collected boiling point	ASTM D1120	°C	-
30°.» - collected boiling point	ASTM D1120	°C	-
40°.» - collected boiling point	ASTM D1120	°C	-
50°.» - collected boiling point	ASTM D1120	°C	-
60°.» - collected boiling point	ASTM D1120	°C	-
70°.» - collected boiling point	ASTM D1120	°C	-
80°.» - collected boiling point	ASTM D1120	°C	-
90°.» - collected boiling point	ASTM D1120	°C	-
95°.» - collected boiling point	ASTM D1120	°C	-
Final boiling point (FBP)	ASTM D1120	°C	220

